

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 8741 (1978): Connecting Lug, Quick Release, Adjustable, PTRM [PGD 14: Consumer Products and Allied Equipments]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE






Indian Standard
**SPECIFICATION FOR
CONNECTING LUG, QUICK RELEASE,
ADJUSTABLE, PTRM**

1. Scope — Dimensional and other requirements for quick release adjustable PTRM connecting lug.

2. Shape and Dimensions — As shown in Fig. 1.



All dimensions in millimetres.

FIG. 1 CONNECTING LUG, QUICK RELEASE, ADJUSTABLE, PTRM

2.1 A deviation of $\begin{smallmatrix} +0.5 \\ -0.0 \end{smallmatrix}$ mm shall be allowed on all dimensions affecting the cross-sections.

2.2 A deviation of $\begin{smallmatrix} -0.5 \\ +0.0 \end{smallmatrix}$ mm shall be allowed on all dimensions shown in Fig. 1.

3. Material — The material shall be steel of any one of the compositions given in Table 1.

3.1 Aircraft quality steel conforming to Designation 40Ni2Cr1Mo28 of IS : 5517-1969 'Specification for steel for hardening and tempering' may also be used.

4. Workmanship and Finish

4.1 All the corners of the lugs shall be properly chamfered.

4.2 All sharp edges and corners shall be rounded off.

Adopted 10 March 1978

© May 1978, ISI

Price Rs 5.00

TABLE 1 CHEMICAL COMPOSITION (PERCENTAGE)

(Clause 3)

SI No.	Type	Carbon	Manga- nese	Phosph- orous	Sulphur	Silicon	Chrom- ium	Nickel	Molyb- denum
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)
i)	Chromium- molybdenum steel	0.38 to 0.43	0.75 to 1.00	0.040 (Max)	0.040 (Max)	0.20 to 0.35	0.80 to 1.10	—	0.15 to 0.25
ii)	Chromium- molybdenum steel	0.28 to 0.33	0.40 to 0.60	0.025 (Max)	0.025 (Max)	0.20 to 0.35	0.80 to 1.10	0.25 (Max)	0.15 to 0.25
iii)	Chromium- nickel- molybdenum steel	0.28 to 0.33	0.70 to 0.90	0.040 (Max)	0.040 (Max)	0.20 to 0.35	0.40 to 0.60	0.40 to 0.70	0.15 to 0.25
iv)	Chromium- nickel- molybdenum steel	0.37 to 0.43	0.70 to 1.05	0.040 (Max)	0.040 (Max)	0.20 to 0.35	0.35 to 0.65	0.35 to 0.75	0.20 to 0.30

4.3 The lugs shall be free from cracks, burrs, pits and other surface defects.

4.4 The lugs shall be free from bend or distortion.

4.5 The lugs shall be plated chromium and nickel over copper. The minimum thickness over the surface shall be copper 0.008 mm, nickel 0.025 mm and chromium 0.000 25 mm. The plating surfaces shall be free from blisters, pits, stain and discolour. The plating shall be uniform throughout and shall be polished bright all over. The plating shall not peel off. The lugs shall be kept at a temperature of 150 to 175°C for a minimum period of half an hour in order to relieve hydrogen embrittlement.

5. Tests

5.1 The lugs shall be uniformly hardened and tempered to give a hardness of 370 to 430 HV.

5.2 The lugs shall be tested for proof load. The proof load shall not be less than 11.18 kN (1 140 kgf).

5.3 The lugs shall be tested for tensile strength. The tensile strength shall be 1 176.80 to 1 314.09 MN/m² (120 to 134 kgf/mm²).

5.4 Crack detention test shall be conducted by the use of a suitable magnetic crack detector prior to plating of the lugs.

5.5 *Adhesion Test* — The plated surface of the lugs shall be rubbed rapidly and firmly for 15 seconds with a smooth copper disc used edgewise. There shall be no indication of the deposition becoming detached from the base metal.

5.6 *Salt Spray Test* — The lugs shall be subjected to 20 percent sodium chloride salt solution spray in a chamber. There shall not be any sign of corrosion on completion of the test.

6. *Marking* — Each lug shall be marked with the manufacturer's name or initials or registered trade-mark.

6.1 *ISI Certification Marking* — Details available with the Indian Standards Institution.

7. *Packing* — The lugs shall be packed as agreed to between the purchaser and the supplier.